

# 6500SS Cooler

Stainless Steel Water Cooler



## Rugged & Reliable

**Closed-loop design with radiator** reduces coolant temperatures and prevents the system from overheating. It also recirculates the coolant through a fan-cooled heat exchanger

**Rustproof coolant reservoir** molded of stainless steel for durability and corrosion resistance.

**Positive vane-style displacement pumps** provide consistent coolant flow and pressure rating with long pump-life expectancy.

**Factory-preset pressure-relief valves (60 PSI)** maintain consistent pressure during operation.

**Thermally protected 1/3 HP motor** guards against motor damage due to overheating.

**Standard inlet/outlet torch fittings** are compatible with TIG and MIG torches having standard 5/8"-18 left-hand fittings.

**10ft (3m) power cords with plugs** are longer than most power cords in the industry —providing the extra length when required.

**Works best with Industrial Supreme Coolant/Antifreeze** and are ideal for warm and cold weather conditions, while providing HF (high frequency) or corrosion protection.



### SPECIFICATIONS

Dimensions	21.25" x 13.13" x 20.75" (54.0cm x 33.3cm x 52.7cm)
Reservoir	6 gallon (22.7L) capacity, stainless steel
Pump Capacity	100 psi max. 1.7 GPM (6.4 lpm)
Heat Exchanger	High efficiency, copper core, rustproof
Motor Voltage	6500SS 115V; 6502SS 230V
Amperage	6500SS 6.4/5.6; 6502SS 3.2/2.8
Water Connections	1/4" N.P.T. Connection (supplied with 5/8"-18 UNF LH thread fittings)
Net Weight	43 lbs (19.5 kg)
Shipping Weight	50 lbs (22.7 kg)

### MODEL SELECTION CHART

Model	BTU/H	Gallons	Volts	Amps	Hz	Phase
6500SS	14,500	6 (22.7L)	115	6.4/5.6	50/60	Single
6502SS	14,500	6 (22.7L)	230	3.2/2.8	50/60	Single

MADE IN **USA**  
GREEN BAY, WI

© 2006 ITW Cooling Systems

p. (920) 429-0000  
f. (920) 429-0002

ITW Cooling Systems  
1018 Circle Drive  
Green Bay, WI 54304